



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7TH Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277
uday.sawant@kei-ind.com / swapnil.kanekar@kei-ind.com



PRICE LIST : FEBRUARY-2020

LP NO. KEI/W&F/LP/19-20/03 DT.16.02.2020

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	595	28	1190	12	6.61
0.75	24/0.20	7	805	28	1610	12	8.94
1.00	32/0.20	11	1005	24	2010	12	11.17
1.50	30/0.25	14	1510	16	3020	8	16.78
2.50	50/0.25	19	2440	12	4880	6	27.11
4.00	56/0.30	26	3605	8	7210	4	40.06
6.00	84/0.30	31	5470	6	10940	3	60.78
10.00	80/0.40	42	9830	1			109.22
16.00	126/0.40	57	15300	1			170.00

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	655	28	1310	12	7.28
0.75	24/0.20	7	835	28	1670	12	9.28
1.00	32/0.20	11	1060	24	2120	12	11.78
1.50	30/0.25	14	1595	16	3190	8	17.72
2.50	50/0.25	19	2560	12	5120	6	28.44
4.00	56/0.30	26	3785	8	7570	4	42.06
6.00	84/0.30	31	5695	6	11390	3	63.28
10.00	80/0.40	42	10380	1			115.33
16.00	126/0.40	57	16190	1			179.89

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	875	28	1750	12	9.72
1.00	32/0.20	11	1135	24	2270	12	12.61
1.50	30/0.25	14	1670	16	3340	8	18.56
2.50	50/0.25	19	2665	12	5330	6	29.61
4.00	56/0.30	26	3875	8	7750	4	43.06
6.00	84/0.30	31	5865	6	11730	3	65.17
10.00	80/0.40	42	10660	1			118.44
16.00	126/0.40	57	16570	1			184.11

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7TH Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,

Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277

uday.sawant@kei-ind.com / swapnil.kanekar@kei-ind.com



PRICE LIST : FEBRUARY-2020

LP NO. KEI/W&F/LP/19-20/03 DT.16.02.2020

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES

HSN CODE : 85.44.60.20

KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	665	705	725	35	276/0.4	110	37720	38980	39540
0.75	24/0.20	7	24	895	935	930	50	396/0.4	145	54090	55960	56710
1.0	32/0.20	12	20	1115	1175	1180	70	354/0.5	200	75830	78410	79390
1.5	30/0.25	16	16	1680	1755	1770	95	484/0.5	235	99860	103870	105150
2.5	50/0.25	22	12	2710	2825	2845	120	608/0.5	270	127720	132500	134870
4.0	56/0.30	29	8	4005	4145	4205	150	750/0.5	310	160050	166080	168130
6	84/0.30	37	4	6080	6305	6330	185	925/0.5	360	193970	201620	204290
10	80/0.40	51	1	10920	11480	11530	240	1210/0.5	425	256050	265910	269840
16	126/0.40	68	1	17000	17900	17990	300	1527/0.5	490	319120	331180	336310
25	196/0.40	86	1	27000	27920	28310	400	2036/0.5	590	422450	431980	437990

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	1960	2600	3230	4380	5070	5540	8590	9920	11320	12920	14920	19090
0.75	24/0.20	2650	3400	4380	6050	6910	7610	11570	13450	15520	17690	20540	26240
1.0	32/0.20	2950	4040	5300	7090	8400	9430	14270	16520	19090	21790	25240	32170
1.5	30/0.25	4040	5650	7280	9850	11570	12970	19290	22690	26290	30010	34860	44630
2.5	50/0.25	6550	9070	11870	15660	18520	20690	30530	36160	42280	48010	56200	71760
4.0	56/0.3	10270	14520	18820	25590	29310	33960	49960	59240	68710	78190	91810	117980

6	84/0.3	14740	21160	27930	36650	
10	80/0.4	25030	35910	47370	62390	
16	126/0.4	38500	55170	72840		
25	196/0.4		89650	117680		
35	276/0.4		124660	162560		
50	396/0.4		178520	233370		
70	354/0.5		246330	324130		
95	484/0.5		0	428850		
120	608/0.5					

Note :

KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	5960
2.5	50/0.25	9230
4	56/0.3	13920
6	84/0.3	20810
10	80/0.4	34210
16	126/0.4	54060
25	196/0.4	81670

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.